

## EP101 Oak Rustic Brushed & UV Oiled



### Product Description

The 150mm x 6mm rustic oak top layer is rolled with steel brushes to take away the softer grain whilst following the contours of the natural grain, the result is an enhanced surface texture which becomes tactile underfoot and extremely durable to everyday scratches. The brushed surface is further enhanced and protected by coats of UV cured oil. This surface whilst keeping the natural feel of the floor is easy to maintain with Wood's Good Natural Soap.

### Product Information

|                                 |   |
|---------------------------------|---|
| USAGE                           | Commercial and Residential Applications                                       |
| Product Code                    | EP101   |
| Name                            | EP101 Oak Rustic Brushed & UV Oiled   |
| Dimensions                      | 150 x 18 x Random mm  |
| Board Type                      | Multi-Ply Engineered hardwood board with tongue & groove profile              |
| Pattern                         | 1 Strip Micro Bevelled  |
| Pack Size                       | 1.65m <sup>2</sup> (Pack includes radom cut boards ranging from 300 - 1500mm) |
| Top layer                       | 3 mm Rustic European Oak  |
| Timber Grade                    | CD Rustic Grade   |
| Surface                         | Sanded & UV Oiled   |
| Suitable for Underfloor Heating | Yes (temperature of top face must not exceed 27°C /See fitting guide)         |
| Guarantee                       | 35 Year Domestic Guarantee (see website for details)                          |
| Commercial Guarantee            | 3 Year Commercial Guarantee (see website for details)                         |

© This technical data sheet was written by V4 Woodflooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

### Grading Criteria - CD Rustic

V4 Woodflooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed please allow for extra material upon installation.

|                              |   |
|------------------------------|---|
| Maximum Size of Sound Knots  | 50 mm Diameter (approx')                |
| Maximum Size of Filled Knots | 30 mm Diameter (approx')                |
| Filled Defects               | Allowed                                 |
| Filler Type                  | Traditional Black and Dark Brown Filler |
| Sap Wood                     | Allowed                                 |
| End Checks                   | Not Allowed                             |
| Heart Wood                   | Allowed                                 |
| Insect Damage                | Not Allowed                             |
| Colour Variation             | Allowed                                 |
| Small Shakes                 | Allowed                                 |
| Ingrown Bark                 | Not Allowed                             |
| Grain Variation              | Allowed                                 |

### General Data

|  |  |
|--|--|
| Country of manufacture                   | China  |
| European Timber Regulation               | Full documented evidence of legality of timber         |
| FSC®                                     | FSC® 100% Certification Available for Project Enquires |
| PEFC®                                    | Not available with this product                        |
| JANKA HARDNESS RATING                    | Oak 1360 lbf (6000N)                                   |
| SLIP RESISTANCE                          | EN 1339 (test result USRV 100)                         |
| EUROPEAN REACTION TO FIRE CLASSIFICATION | EN 13501-1 (test result: Dn - S1)                      |
| THERMAL CONDUCTIVITY                     | EN 12524 (Test result: 0.16W/mK)                       |
| RELEASE OF FORMALDEHYDE                  | EN 717-1 (Test result $\leq$ 0.012mg/m <sup>3</sup> )  |
| STAIN RESISTANCE                         | Good resistance in conjunction proper maintenance      |
| SLIP RESISTANCE                          | EN 1339 (test result USRV 100)                         |

© This technical data sheet was written by V4 Woodflooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

### Installation Method

V4 Woodflooring® should be fitted in accordance with our installation guides by experienced flooring installers for more information visit [www.v4woodflooring.co.uk](http://www.v4woodflooring.co.uk).

|                         |   |
|-------------------------|---|
| Fully Bonded            | Yes (Recommended)   |
| Secret Nailed           | Yes   |
| Floated on Underlay     | Yes   |
| Over Underfloor heating | Yes (fully bonded recommended)<br>Temperature of top surface should not exceed 27°C |

### Cleaning & Maintenance - Domestic Schedule

Floors should be kept clean and free from dust and grit. It is recommended that high traffic areas and kitchen areas are given an initial application of Wood's Good Natural Floor Care Refresher.

**Note: Avoid soaking the floor with water. Use a Wood's Good Applicator Pad or a well wrung mop.**

| RECOMMENDED PRODUCTS*                    | INITIAL | REGULAR | 6 OR 12 MONTHLY<br>(DEPENDING ON USE) |
|--|---------|---------|---------------------------------------|
| WOOD'S GOOD NATURAL CARE SOAP SPRAY      |         | √       |                                       |
| WOOD'S GOOD NATURAL FLOOR CARE REFRESHER | √       |         | √                                     |

\* Visit [www.v4woodflooring.co.uk](http://www.v4woodflooring.co.uk) for detailed advice on using the above products.

### Cleaning & Maintenance - Commercial Schedule

Floors should be kept clean and free from dust and grit. It is recommended that high traffic areas and kitchen areas are given an initial and regular application of Wood's Good Natural Floor Care Refresher.

**Note: Avoid soaking the floor with water. Use a Wood's Good Applicator Pad or a well wrung mop.**

| RECOMMENDED PRODUCTS*   | INITIAL | REGULAR | 1 OR 6 MONTHLY<br>(DEPENDING ON USE) |
|---|---------|---------|--------------------------------------|
| WOOD'S GOOD NATURAL CARE SOAP SPRAY<br>OR<br>WOOD'S GOOD NATURAL FLOOR CARE REFRESHER DILUTED |         | √       |                                      |
| WOOD'S GOOD NATURAL FLOOR CARE REFRESHER  | √       |         | √                                    |

\* Visit [www.v4woodflooring.co.uk](http://www.v4woodflooring.co.uk) for detailed advice on using the above products.