bring nature inside™
v4woodflooring.co.uk

V4 Wood Flooring®
Technical Data Sheet

IM303 Degas

Pictured: Plank Format (Available in various formats see details below)

Product Details

Product Code	IM303
Collection	Impressions, Craft
Construction	Engineered
Species	Oak
Product Type	Engineered Plank
Surface	Distressed, Reactive Stained, Colour Oiled
Finish	Natural Oil
Plank Dimensions (mm)	W180 / 220 x D15 x L1500-2500
Herringbone Dimensions (mm)	W100 x D15 x L600
Top Layer	4mm - Solid European Oak
Core Layer	11 mm – Birch Plywood
Available Grade(s)	Rustic
Pack Size	Wrapped in random amounts
Pack Contents	N/A
Joint Type	Tongue & Grooved
Edge Profile	Bevel Edged on 2 sides

Technical Information

Country of Manufacture	Belgium
EUTR/ European Timber Regulation	Full documented evidence of legality of timber
FSC® Certification	Not available with this product
PEFC® Certification	Not available with this product
Janka Hardness	Oak 1360 lbf (6000N)
Slip Resistance	Please enquire at technical@v4woodflooring.co.uk
European Reaction to Fire Classification	Dfl-S1
Release of Formaldehyde	EN 717-1 (Test result E1)
Thermal Conductivity	EN 12524 Test result: 0.17 W/(mK)

Grading: Rustic

Bigger rustic circular open filled knots, cross-shaped and other shaped knots unlimited and cracks filled allowed. Closed healthy knots unlimited and sapwood allowed. No pinholes, insects or molding mistakes, combed grain and different grain flow occasionally permitted, mineral streaks can occur in small amount due to influence oxidative natural process

Installation Methods

All V4 floors should be installed by experienced flooring installers who have read and understood the appropriate installation guides at www.v4woodflooring.co.uk

Plank Installation	
Fully Bonded	Yes*
Secret Nailed	No
Floated on Underlay	Yes*
Over Underfloor Heating	Yes* (fully bonded installation recommended)

Herringbone Installation	
Fully Bonded	Yes * (Must always be fully bonded)

Maintenance Advice

Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Use PH neutral cleaners and avoid soaking the floor with water. For more detailed advice visit www.v4woodflooring.co.uk

EUTR COMPLIANT

V4 Wood Flooring®

Call +44(0)1276 488099
Email team@v4woodflooring.co.uk
Visit www.v4woodflooring.co.uk

*Subject to correctly prepared and compatible subfloor and in conjunction with correct installation

© This technical data sheet was written by V4 Wood Flooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.