



Technical Information

Country of Manufacture	Belgium
EUTR/ European Timber Regulation	Full documented evidence of legality of timber
FSC® Certification	Not available with this product
PEFC® Certification	Not available with this product
Janka Hardness	Oak 1360 lbf (6000N)
Slip Resistance	Please enquire at technical@v4woodflooring.co.uk
European Reaction to Fire Classification	Dfl-S1
Release of Formaldehyde	EN 717-1 (Test result E1)
Thermal Conductivity	EN 12524 Test result: 0.17 W/(mK)

Grading: Special Rustic

Bigger rustic circular open filled knots, cross-shaped and other shaped knots unlimited and cracks filled allowed. Closed healthy knots unlimited and sapwood allowed. No pinholes, insects or molding mistakes, combed grain and different grain flow occasionally permitted, mineral streaks can occur in small amount due to influence oxidative natural process

Installation Methods

All V4 floors should be installed by experienced flooring installers who have read and understood the appropriate installation guides at www.v4woodflooring.co.uk

Plank Installation

Fully Bonded	Yes*
Secret Nailed	No
Floated on Underlay	Yes*
Over Underfloor Heating	Yes* (fully bonded installation recommended)

Herringbone Installation

Fully Bonded	Yes * (Must always be fully bonded)
--------------	-------------------------------------

Product Details

Product Code	IM308
Collection	Impressions, Aged
Construction	Engineered
Species	Oak
Product Type	Engineered Plank
Surface	Aged, Distressed, Sawn, Unfilled
Finish	Natural Oil
Dimensions (mm)	W 190 x D 15 x L 1900
Top Layer	4mm - Solid European Oak
Core Layer	11 mm – Birch Plywood
Available Grade(s)	Special Rustic
Pack Size	Wrapped in random amounts
Pack Contents	N/A
Joint Type	Tongue & Grooved
Edge Profile	Bevel Edged on 2 sides

Maintenance Advice

Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Use PH neutral cleaners and avoid soaking the floor with water. For more detailed advice visit www.v4woodflooring.co.uk

